



### Brazed heat exchangers

Type name	Connection size [DN]	Connection type	Width [mm]	Length [mm]	Max design pressure [bar]	Max working temperature [°C]	
XB 04	3/4"	Thread	93	296	25	180	
XB 05	3/4"	Thread	76	312			
XB 06	3/4"	Thread	95	320			
XB 10	1"	Thread	118	288			
XB 20	1"	Thread	118	338			
XB 24	3/4"	Thread	93	490			
XB 30	1"	Thread	118	438			
XB 37	1"	Thread	119	525			
XB 51	2"	Thread+flange	253	462			
XB 59	2"	Thread	188	613			
XB 61	2"	Thread+flange	243	525			
XB 66	2½"	Flange	296	706			
XB 70	65/100	Flange	365	991			25/16

### Gasketed heat exchangers

XG 10	1"	Thread	158	310	16	150	
XG 14	1¼"	Thread	200	560			
XG 18	1¼"	Thread	200	760			
XG 20	2"	Thread	300	835			
XG 30	65	Flange	360	910			
XG 31	65	Flange	360	910			
XGM 032	32	Thread	160	600			25
XGF 100-34	100	Flange	510	1185			
XGF 100-35	100	Flange	510	1185			
XGF 100-50	100	Flange	510	1603			
XGF 100-66	100	Flange	510	2021			
XGC 008	32	Thread	180	774			
XGC 009	40	Thread	250	725			
XGC 013	50	Thread	320	832			
XGC 016	50	Thread	320	832			
XGC 026	100	Flange	450	1265			
XGC 042	100	Flange	450	1520			
XGC 044	100	Flange	450	1675			
XGC 051	150	Flange	585	1730			
XGC 054	150	Flange	630	1730			
XGC 091	150	Flange	626	2390			
XGC 118	150	Flange	626	2870			
XGC 060	200	Flange	825	1700			
XGC 100	200	Flange	825	2280			
XGC 140	200	Flange	825	2860			
XGC 085	300	Flange	1060	1985			
XGC 145	300	Flange	1060	2565			
XGC 205	300	Flange	1060	3215			
XGC 265	300	Flange	1060	3795			
XGC 325	300	Flange	1060	4375			
XGC 230	500	Flange	1510	3172			
XGC 330	500	Flange	1510	3782			
XGC 430	500	Flange	1510	4392			